

FCC Verification Test Report

Report No.: FV160628D07

Test Model: EMBC-1000-600U

Series Model: EMBC-1XXXX-XXXX series
("X" can be 0-9, A-Z or blank for marketing purpose)

Received Date: Jun. 30, 2016

Test Date: Jul. 11, 2016

Issued Date: Aug. 3, 2016

Applicant: Vecow Co., Ltd.

Address: 12F., No. 111, Zhongcheng Rd., Tucheng Dist., New Taipei City 23674
Taiwan (R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

| | |
|--|-----------|
| Release Control Record..... | 3 |
| 1 Certificate of Conformity..... | 4 |
| 2 Summary of Test Results..... | 5 |
| 2.1 Measurement Uncertainty..... | 5 |
| 2.2 Modification Record..... | 5 |
| 3 General Information | 6 |
| 3.1 Features of EUT..... | 6 |
| 3.2 General Description of EUT..... | 6 |
| 3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode..... | 8 |
| 3.4 Test Program Used and Operation Descriptions | 8 |
| 3.5 Primary Clock Frequencies of Internal Source | 8 |
| 4 Configuration and Connections with EUT..... | 9 |
| 4.1 Connection Diagram of EUT and Peripheral Devices | 9 |
| 4.2 Configuration of Peripheral Devices and Cable Connections..... | 10 |
| 5 Conducted Emissions at Mains Ports | 11 |
| 5.1 Limits | 11 |
| 5.2 Test Instruments..... | 11 |
| 5.3 Test Arrangement..... | 12 |
| 5.4 Test Results | 13 |
| 6 Radiated Emissions up to 1 GHz..... | 15 |
| 6.1 Limits | 15 |
| 6.2 Test Instruments..... | 16 |
| 6.3 Test Arrangement..... | 17 |
| 6.4 Test Results | 18 |
| 7 Radiated Emissions above 1 GHz | 20 |
| 7.1 Limits | 20 |
| 7.2 Test Instruments..... | 21 |
| 7.3 Test Arrangement..... | 22 |
| 7.4 Test Results | 23 |
| 8 Pictures of Test Arrangements | 25 |
| 8.1 Conducted Emissions at Mains Ports..... | 25 |
| 8.2 Radiated Emissions up to 1 GHz..... | 26 |
| 8.3 Radiated Emissions above 1 GHz | 27 |
| Appendix – Information on the Testing Laboratories..... | 28 |

Release Control Record

| Issue No. | Description | Date Issued |
|-------------|-------------------|--------------|
| FV160628D07 | Original release. | Aug. 3, 2016 |

1 Certificate of Conformity

Product: Motherboard

Brand: Vecow

Test Model: EMBC-1000-600U

Series Model: EMBC-1XXXX-XXXX series("X" can be 0-9, A-Z or blank for marketing purpose)

Sample Status: Engineering sample


Applicant: Vecow Co., Ltd.

Test Date: Jul. 11, 2016

Standards: 47 CFR FCC Part 15, Subpart B, Class A
ICES-003:2016 Issue 6, Class A
ANSI C63.4:2014

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :



Jessica Cheng / Senior Specialist

Date: Aug. 3, 2016

Approved by :



Henry Lai / Director

Date: Aug. 3, 2016

2 Summary of Test Results

47 CFR FCC Part 15, Subpart B / ICES-003:2016 Issue 6, Class A

ANSI C63.4:2014

| FCC Clause | ICES-003 Clause | Test Item | Result/Remarks | Verdict |
|------------|-----------------|-----------------------------------|--|---------|
| 15.107 | 6.1 | AC Power Line Conducted Emissions | Minimum passing Class A margin is -17.87 dB at 0.17734 MHz | Pass |
| 15.109 | 6.2.1 | Radiated Emissions up to 1 GHz | Minimum passing Class A margin is -2.01 dB at 742.50 MHz | Pass |
| | 6.2.2 | Radiated Emissions above 1 GHz | Minimum passing Class A margin is -8.61 dB at 2227.50 MHz | Pass |

Note: There is no deviation to the applied test methods and requirements covered by the scope of this report.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

| Measurement | Frequency | Expanded Uncertainty (k=2) (\pm) |
|------------------------------------|----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 2.78 dB |
| Radiated Emissions up to 1 GHz | 30MHz ~ 1GHz | 3.73 dB |
| Radiated Emissions above 1 GHz | Above 1GHz | 3.36 dB |

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 Features of EUT

The tests reported herein were performed according to the method specified by Vecow Co., Ltd., for detailed feature description, please refer to the manufacturer's specifications or user's manual.

3.2 General Description of EUT

| | |
|---------------------|---|
| Product | Motherboard |
| Brand | Vecow |
| Test Model | EMBC-1000-600U |
| Series Model | EMBC-1XXXX-XXXX series("X" can be 0-9, A-Z or blank for marketing purpose) |
| Model Difference | For marketing purpose |
| Sample Status | Engineering sample |
| Operating Software | Windows 10, Windows 8.1, Windows 7, Linux |
| Power Supply Rating | 12V to 36V, DC-in Refer to table as below |
| Accessory Device | N/A |
| Data Cable Supplied | N/A |

Note:

1. The EUT was installed in platform during the test.
2. The platform product & brand & model as below

| Product | Brand | Test Model | Interfaces |
|---------------------------------------|-------|---------------|---|
| Ultra-compact Fanless Embedded Box PC | Vecow | SPC-3530-600U | 2 COM*9 (RS-232/ 422/ 485) |
| | | | 2 USB 3.0*4 |
| | | | 2 Isolated DIO*16 (DI*8, DO*8) |
| | | | 2 DVI (resolution up to 1920 x 1080 @ 60Hz) |
| | | | 2 Display (resolution up to 3840 x 2160 @ 30Hz) |
| | | | 2 Line out |
| | | | 2 Mic. in |
| | | | 2 LAN (10/100/1000Mbps)*4 |
| | | | 2 DC input |

3. The platform was configured with the following key components:

| Component | Brand | Model No. or P/N | Spec. | Interfaces |
|-------------------------------------|-----------|------------------------|-----------------------|--|
| CPU(on EUT) | Intel | Core™ i7-6600U | 3.4GHz | - |
| Motherboard (EUT) | Vecow | EMBC-1XXXX-XXXX series | -- | 2 COM*1 (RS-232/ 422/ 485) 2 USB 3.0*4 2 DVI (resolution up to 1920 x 1080 @ 60Hz) 2 Display (resolution up to 3840 x 2160 @ 30Hz) 2 LAN (10/100/1000Mbps)*2 |
| Memory | Transcend | C71906-0010 | 8GB 2Rx8 DDR4 2133 SO | - |
| HDD | HITACHI | HTS542580K9SA00 | 80GB | - |
| 4-port RS-232/ 422/ 485 Serial Card | Vecow | SMX-100 | RS-232/ 422/ 485 | - |
| Mini PCIe 2-port Gigabit LAN Card | Vecow | LMX-200 | 10/100/1000Mbps | - |

4. The platform uses following adapter.

| | |
|--------------|--|
| Brand | MW |
| Model | GS160A24 |
| Input Power | 100-240Vac, 50/60Hz, 2.0A |
| Output Power | 24V, 6.67A, 160W max. |
| Power Line | Non-shielded DC (1.2m) with one ferrite core |

3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode

The platform with EUT is designed with AC power of rating 100-240Vac, 50/60Hz.

For radiated emission evaluation, 230Vac/50Hz & 110Vac/60Hz (for EN 55032), 120Vac/60Hz (for FCC Part 15) had been covered during the pre-test. The worst data was found at **110Vac/60Hz** and recorded in the applied test report. Then the other test items were tested at 120Vac/60Hz.

Test modes are presented in the report as below.

| Mode | Test Condition |
|-------------------------|--|
| Conducted emission test | |
| 1 | Full system, Display (3840 x 2160, 30Hz) + DVI (1920 x 1080, 60Hz) |
| Radiated emission test | |
| 1 | Full system, Display (3840 x 2160, 30Hz) + DVI (1920 x 1080, 60Hz) |

3.4 Test Program Used and Operation Descriptions

- a. Installed the EUT into platform.
- b. Turned on the power of all equipment.
- c. EUT ran a test program to enable all functions.
- d. EUT read and wrote messages from/to HDD/SSD and external HDDs.
- e. EUT sent and received messages to/from Notebook PCs (kept in a remote area) via four UTP LAN cables.
- f. EUT sent "H" messages to ext. LCD Monitors. Then they displayed "H" patterns on their screens simultaneously.
- g. EUT sent 1kHz audio signal to earphone.
- h. EUT sent messages to modems.
- i. EUT sent messages to printer. Then it printed them out simultaneously.
- j. Steps c-i were repeated.


3.5 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 3400 MHz, provided by Vecow Co., Ltd., for detailed internal source, please refer to the manufacturer's specifications.

4 Configuration and Connections with EUT

4.1 Connection Diagram of EUT and Peripheral Devices

TEST CONFIGURATION



4.2 Configuration of Peripheral Devices and Cable Connections

| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|---|------------|------------------------|-----------------|------------------|--------------------|
| A. | LCD Monitor | ASUS | PB287QR | N/A | FCC DoC Approved | Provided by Lab |
| B. | LCD Monitor | View Sonic | VG2860mhl | N/A | FCC DoC Approved | Provided by Lab |
| C. | USB KEYBOARD | BTC | 5200U | G09302046630 | E5XKB5122U | Provided by Lab |
| D. | USB Mouse | Microsoft | 1113 | 9170515772199 | FCC DoC Approved | Provided by Lab |
| E. | USB PRINTER | LEXMARK | Z33 | N/A | FCC DoC Approved | Provided by Lab |
| F. | USB 3.0 Hard Disk | WD | WDBUZG0010BB K-PESN | WX61A45JRTS8 | FCC DoC Approved | Provided by Lab |
| G. | EARPHONE | PHILIPS | SBC HL145 | N/A | N/A | Provided by Lab |
| H. | MICROPHONE | Labtec | mic-333 | N/A | N/A | Provided by Lab |
| I. | MODEM | ACEEX | 1414 | 980020569 | IFAXDM1414 | Provided by Lab |
| | MODEM | ACEEX | 1414 | 980020532 | IFAXDM1414 | Provided by Lab |
| | MODEM | ACEEX | 1414 | 980020534 | IFAXDM1414 | Provided by Lab |
| | MODEM | ACEEX | 1414 | 980020538 | IFAXDM1414 | Provided by Lab |
| J. | COM Load*5 | N/A | N/A | N/A | N/A | Supplied by client |
| K. | Notebook PC | DELL | P41G | HT4W952 | FCC DoC Approved | Provided by Lab |
| | Notebook PC | SONY | SVS151A12P | 275548477001024 | FCC DoC Approved | Provided by Lab |
| | Notebook PC | DELL | P41G | 6BZY242 | FCC DoC Approved | Provided by Lab |
| | Notebook PC | DELL | PP27L | 8SNZ12S | FCC DoC Approved | Provided by Lab |
| L. | Ultra-compact Fanless Embedded Box PC | Vecow | SPC-3530-600U | N/A | Verification | Supplied by client |
| M. | AC adapter | MW | GS160A24 | N/A | FCC DoC Approved | Supplied by client |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items K acted as communication partners to transfer data.
3. The EUT was installed in Item L.

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|-----|---------------|------|------------|-----------------------|--------------|--------------------|
| 1. | Display cable | 1 | 1.5 | Y | 0 | Provided by Lab |
| 2. | DVI cable | 1 | 1.8 | Y | 2 | Provided by Lab |
| 3. | USB cable | 1 | 1.5 | Y | 0 | Provided by Lab |
| 4. | USB cable | 1 | 1.8 | Y | 1 | Provided by Lab |
| 5. | USB cable | 1 | 1.8 | Y | 0 | Provided by Lab |
| 6. | USB cable | 1 | 0.5 | Y | 0 | Provided by Lab |
| 7. | Audio cable | 1 | 1.0 | N | 0 | Provided by Lab |
| 8. | Audio cable | 1 | 2.2 | N | 0 | Provided by Lab |
| 9. | DC cable | 1 | 1.2 | N | 1 | Supplied by client |
| 10. | AC power cord | 1 | 1.8 | N | 0 | Provided by Lab |
| 11. | RS232 cable | 4 | 1.0 | Y | 0 | Provided by Lab |
| 12. | LAN cable | 4 | 10.0 | N | 0 | Provided by Lab |
| 13. | Data cable | 3 | 1.0 | N | 0 | Supplied by client |

Note: The core(s) is(are) originally attached to the cable(s).

5 Conducted Emissions at Mains Ports

5.1 Limits

| Frequency (MHz) | Class A (dBUV) | | Class B (dBUV) | |
|-----------------|----------------|---------|----------------|---------|
| | Quasi-peak | Average | Quasi-peak | Average |
| 0.15 - 0.5 | 79 | 66 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 73 | 60 | 56 | 46 |
| 5.0 - 30.0 | 73 | 60 | 60 | 50 |

Notes: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases linearly with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Test Instruments


| Description & Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due |
|--|-------------|--------------|---------------|---------------|
| ROHDE & SCHWARZ TEST RECEIVER | ESCS 30 | 100276 | Apr. 12, 2016 | Apr. 11, 2017 |
| ROHDE & SCHWARZ Artificial Mains Network (for EUT) | ENV216 | 101197 | May 04, 2016 | May 03, 2017 |
| LISN With Adapter (for EUT) | AD10 | C10Ada-002 | May 04, 2016 | May 03, 2017 |
| ROHDE & SCHWARZ Artificial Mains Network (for peripherals) | ESH3-Z5 | 100218 | Nov. 25, 2015 | Nov. 24, 2016 |
| SCHWARZBECK Artificial Mains Network (For EUT) | NNLK8129 | 8129229 | May 04, 2016 | May 03, 2017 |
| Software | Cond_V7.3.7 | NA | NA | NA |
| RF cable (JYEBAO) With 10dB PAD | 5D-FB | Cable-C10.01 | Feb. 15, 2016 | Feb. 14, 2017 |
| SUHNER Terminator (For ROHDE & SCHWARZ LISN) | 65BNC-5001 | E1-011484 | May 12, 2016 | May 11, 2017 |
| ROHDE & SCHWARZ Artificial Mains Network (For TV EUT) | ESH3-Z5 | 100220 | Nov. 13, 2015 | Nov. 12, 2016 |
| LISN With Adapter (for TV EUT) | 100220 | N/A | Nov. 13, 2015 | Nov. 12, 2016 |

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in Shielded Room No. 10.
 3. The VCCI Site Registration No. C-1852.
 4. Tested Date: Jul. 11, 2016.

5.3 Test Arrangement

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



Note: Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


5.4 Test Results

| | | | |
|-----------------|----------------|--|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 24°C, 76%RH |
| Tested by | Chiawei Lin | | |
| Test Mode | Mode 1 | | |

| Phase Of Power : Line (L) | | | | | | | | | | |
|---------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | | Emission Level (dBuV) | | Limit (dBuV) | | Margin (dB) | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.17734 | 9.70 | 43.54 | 38.01 | 53.24 | 47.71 | 79.00 | 66.00 | -25.76 | -18.29 |
| 2 | 0.25462 | 9.70 | 41.11 | 37.24 | 50.81 | 46.94 | 79.00 | 66.00 | -28.19 | -19.06 |
| 3 | 0.50665 | 9.70 | 27.46 | 21.79 | 37.16 | 31.49 | 73.00 | 60.00 | -35.84 | -28.51 |
| 4 | 0.75156 | 9.72 | 23.44 | 16.24 | 33.16 | 25.96 | 73.00 | 60.00 | -39.84 | -34.04 |
| 5 | 9.37500 | 9.91 | 24.32 | 23.18 | 34.23 | 33.09 | 73.00 | 60.00 | -38.77 | -26.91 |
| 6 | 22.57031 | 9.96 | 23.56 | 19.99 | 33.52 | 29.95 | 73.00 | 60.00 | -39.48 | -30.05 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




| | | | |
|------------------------|----------------|---|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 24°C, 76%RH |
| Tested by | Chiawei Lin | | |
| Test Mode | Mode 1 | | |

| Phase Of Power : Neutral (N) | | | | | | | | | | |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | | Emission Level (dBuV) | | Limit (dBuV) | | Margin (dB) | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.17734 | 9.69 | 43.73 | 38.44 | 53.42 | 48.13 | 79.00 | 66.00 | -25.58 | -17.87 |
| 2 | 0.25284 | 9.69 | 42.39 | 36.81 | 52.08 | 46.50 | 79.00 | 66.00 | -26.92 | -19.50 |
| 3 | 0.50539 | 9.70 | 28.43 | 22.15 | 38.13 | 31.85 | 73.00 | 60.00 | -34.87 | -28.15 |
| 4 | 0.75156 | 9.71 | 22.15 | 15.29 | 31.86 | 25.00 | 73.00 | 60.00 | -41.14 | -35.00 |
| 5 | 9.37500 | 9.90 | 25.26 | 24.11 | 35.16 | 34.01 | 73.00 | 60.00 | -37.84 | -25.99 |
| 6 | 22.57031 | 9.95 | 24.22 | 21.20 | 34.17 | 31.15 | 73.00 | 60.00 | -38.83 | -28.85 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



6 Radiated Emissions up to 1 GHz

6.1 Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

| Radiated Emissions Limits at 10 meters (dB μ V/m) | | | | |
|---|-----------------------------|-----------------------------|-------------------|-------------------|
| Frequencies (MHz) | FCC 15B / ICES-003, Class A | FCC 15B / ICES-003, Class B | CISPR 22, Class A | CISPR 22, Class B |
| 30-88 | 39 | 29.5 | 40 | 30 |
| 88-216 | 43.5 | 33.1 | | |
| 216-230 | 46.4 | 35.6 | | |
| 230-960 | | 47 | 37 | |
| 960-1000 | 49.5 | 43.5 | | |

| Radiated Emissions Limits at 3 meters (dB μ V/m) | | | | |
|--|-----------------------------|-----------------------------|-------------------|-------------------|
| Frequencies (MHz) | FCC 15B / ICES-003, Class A | FCC 15B / ICES-003, Class B | CISPR 22, Class A | CISPR 22, Class B |
| 30-88 | 49.5 | 40 | 50.5 | 40.5 |
| 88-216 | 54 | 43.5 | | |
| 216-230 | 56.9 | 46 | | |
| 230-960 | | 57.5 | 47.5 | |
| 960-1000 | 60 | 54 | | |

- Notes:
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
 3. QP detector shall be applied if not specified.

6.2 Test Instruments


| Description & Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due |
|-------------------------------------|----------------------|--------------|---------------|---------------|
| ROHDE & SCHWARZ TEST RECEIVER | ESCI | 100744 | Apr. 28, 2016 | Apr. 27, 2017 |
| Schaffner BILOG Antenna | CBL6111D | 22270 | Jan. 05, 2016 | Jan. 04, 2017 |
| CT Turn Table | TT100 | CT-080 | NA | NA |
| CT Tower | AT100 | CT-080 | NA | NA |
| Software | Radiated_V7.6.15.9.4 | NA | NA | NA |
| ANRITSU RF Switches | MP59B | N/A | Mar. 11, 2016 | Mar. 10, 2017 |
| WOKEN RF cable With 5dB PAD | 8D | CABLE-ST3-01 | Mar. 11, 2016 | Mar. 10, 2017 |

- Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Open Site No. 3.
 3. The VCCI Site Registration No. is R-269.
 4. The FCC Site Registration No. 90424.
 5. Tested Date: Jul. 11, 2016.

6.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is up to 1 GHz.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency up to 1GHz.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.4 Test Results


| | | | |
|------------------------|--------------|---|-------------------------|
| Frequency Range | 30MHz ~ 1GHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP), 120kHz |
| Tested by | Hermes Lin | Environmental Conditions | 31°C, 75%RH |
| Test Mode | Mode 1 | | |

Antenna Polarity & Test Distance : Horizontal at 10 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----------|-----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 64.22 | 28.36 QP | 40.00 | -11.64 | 4.00 H | 62 | 16.51 | 11.85 |
| 2 | 74.37 | 27.74 QP | 40.00 | -12.26 | 4.00 H | 149 | 14.88 | 12.86 |
| 3 | 108.77 | 25.74 QP | 40.00 | -14.26 | 4.00 H | 191 | 8.67 | 17.07 |
| 4 | 125.00 | 34.36 QP | 40.00 | -5.64 | 4.00 H | 0 | 16.40 | 17.96 |
| 5 | 148.56 | 27.58 QP | 40.00 | -12.42 | 4.00 H | 195 | 10.12 | 17.46 |
| 6 | 184.32 | 24.56 QP | 40.00 | -15.44 | 4.00 H | 122 | 9.27 | 15.29 |
| 7 | 222.80 | 31.51 QP | 40.00 | -8.49 | 4.00 H | 217 | 15.28 | 16.23 |
| 8 | 296.94 | 30.95 QP | 47.00 | -16.05 | 4.00 H | 132 | 10.62 | 20.33 |
| 9 | 397.06 | 43.95 QP | 47.00 | -3.05 | 4.00 H | 341 | 20.68 | 23.27 |
| 10 | 445.51 | 34.83 QP | 47.00 | -12.17 | 1.99 H | 203 | 10.18 | 24.65 |
| 11 | 742.50 | 44.99 QP | 47.00 | -2.01 | 1.38 H | 297 | 41.71 | 3.28 |
| 12 | 891.00 | 44.62 QP | 47.00 | -2.38 | 1.00 H | 14 | 39.86 | 4.76 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




| | | | |
|------------------------|--------------|---|-------------------------|
| Frequency Range | 30MHz ~ 1GHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP), 120kHz |
| Tested by | Hermes Lin | Environmental Conditions | 31°C, 75%RH |
| Test Mode | Mode 1 | | |

Antenna Polarity & Test Distance : Vertical at 10 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 30.87 | 35.53 QP | 40.00 | -4.47 | 1.00 V | 166 | 38.69 | -3.16 |
| 2 | 66.11 | 33.73 QP | 40.00 | -6.27 | 1.00 V | 276 | 21.78 | 11.95 |
| 3 | 74.22 | 36.00 QP | 40.00 | -4.00 | 1.00 V | 244 | 23.15 | 12.85 |
| 4 | 111.39 | 36.94 QP | 40.00 | -3.06 | 1.00 V | 235 | 19.71 | 17.23 |
| 5 | 125.00 | 32.07 QP | 40.00 | -7.93 | 1.00 V | 284 | 14.11 | 17.96 |
| 6 | 148.48 | 31.17 QP | 40.00 | -8.83 | 1.00 V | 245 | 13.70 | 17.47 |
| 7 | 184.32 | 25.92 QP | 40.00 | -14.08 | 1.00 V | 193 | 10.63 | 15.29 |
| 8 | 222.80 | 28.83 QP | 40.00 | -11.17 | 1.00 V | 118 | 12.60 | 16.23 |
| 9 | 296.94 | 34.07 QP | 47.00 | -12.93 | 1.00 V | 205 | 13.74 | 20.33 |
| 10 | 408.20 | 36.26 QP | 47.00 | -10.74 | 1.00 V | 108 | 12.43 | 23.83 |
| 11 | 445.61 | 29.76 QP | 47.00 | -17.24 | 1.25 V | 357 | 5.11 | 24.65 |
| 12 | 499.99 | 39.95 QP | 47.00 | -7.05 | 1.57 V | 240 | 14.23 | 25.72 |
| 13 | 742.50 | 43.90 QP | 47.00 | -3.10 | 2.67 V | 318 | 40.62 | 3.28 |
| 14 | 891.00 | 43.86 QP | 47.00 | -3.14 | 1.62 V | 171 | 39.10 | 4.76 |
| 15 | 928.50 | 40.30 QP | 47.00 | -6.70 | 1.48 V | 209 | 7.48 | 32.82 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



7 Radiated Emissions above 1 GHz

7.1 Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

| Radiated Emissions Limits at 10 meters (dB μ V/m) | | | | |
|---|-----------------------------|-----------------------------|-------------------|-------------------|
| Frequencies (MHz) | FCC 15B / ICES-003, Class A | FCC 15B / ICES-003, Class B | CISPR 22, Class A | CISPR 22, Class B |
| 1000-3000 | Avg: 49.5 | Avg: 43.5 | Not defined | Not defined |
| Above 3000 | Peak: 69.5 | Peak: 63.5 | Not defined | Not defined |

| Radiated Emissions Limits at 3 meters (dB μ V/m) | | | | |
|--|-----------------------------|-----------------------------|---------------------|---------------------|
| Frequencies (MHz) | FCC 15B / ICES-003, Class A | FCC 15B / ICES-003, Class B | CISPR 22, Class A | CISPR 22, Class B |
| 1000-3000 | Avg: 60 | Avg: 54 | Avg: 56 Peak: 76 | Avg: 50 Peak: 70 |
| Above 3000 | Peak: 80 | Peak: 74 | Avg: 60 Peak: 80 | Avg: 54 Peak: 74 |

- Notes: 1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Frequency Range (For unintentional radiators)

| Highest frequency generated or used in the device or on which the device operates or tunes (MHz) | Upper frequency of measurement range (MHz) |
|--|--|
| Below 1.705 | 30 |
| 1.705-108 | 1000 |
| 108-500 | 2000 |
| 500-1000 | 5000 |
| Above 1000 | 5th harmonic of the highest frequency or 40GHz, whichever is lower |

7.2 Test Instruments


| Description & Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due |
|---------------------------------|---------------------|----------------|---------------|---------------|
| Agilent Spectrum | E4446A | MY51100009 | May 30, 2016 | May 29, 2017 |
| Agilent Test Receiver | N9038A | MY50010135 | Jul. 18, 2015 | Jul. 17, 2016 |
| Agilent Preamplifier | 8449B | 3008A02367 | Feb. 27, 2016 | Feb. 26, 2017 |
| MITEQ Preamplifier | AMF-6F-260400-33-8P | 892164 | Mar. 01, 2016 | Feb. 28, 2017 |
| EMCI Preamplifier | EMC184045B | 980235 | Mar. 01, 2016 | Feb. 28, 2017 |
| Schwarzbeck Horn Antenna | BBHA-9170 | 212 | Jan. 08, 2016 | Jan. 07, 2017 |
| EMCO Horn Antenna | 3115 | 9312-4192 | Jan. 18, 2016 | Jan. 17, 2017 |
| Max Full. Turn Table & Tower | MF7802 | MF780208103 | NA | NA |
| Software | Radiated_V8.7.07 | NA | NA | NA |
| SUHNER RF cable With 4dB PAD | SF106-18 | Cable-CH7 | Aug. 15, 2015 | Aug. 14, 2016 |
| SUHNER RF cable With 3dB PAD | SF102 | Cable-CH8-3.6m | Aug. 15, 2015 | Aug. 14, 2016 |

- Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Chamber No. 7.
3. The Industry Canada Reference No. IC 7450E-7.
4. The FCC Site Registration No. 127748.
5. The VCCI Site Registration No. G-39.
6. Tested Date: Jul. 11, 2016.

7.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The spectrum analyzer system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

Note: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.



* :depends on the EUT height and the antenna 3dB beamwidth both.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


7.4 Test Results

| | | | |
|------------------------|--------------|---|--------------------------------|
| Frequency Range | 1GHz ~ 17GHz | Detector Function & Resolution Bandwidth | Peak (PK) / Average (AV), 1MHz |
| Tested by | Vincent Chen | Environmental Conditions | 23°C, 73%RH |
| Test Mode | Mode 1 | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2079.02 | 60.03 PK | 80.00 | -19.97 | 1.95 H | 181 | 59.09 | 0.94 |
| 2 | 2079.02 | 46.65 AV | 60.00 | -13.35 | 1.95 H | 181 | 45.71 | 0.94 |
| 3 | 2227.50 | 57.08 PK | 80.00 | -22.92 | 2.00 H | 126 | 55.99 | 1.09 |
| 4 | 2227.50 | 47.49 AV | 60.00 | -12.51 | 2.00 H | 126 | 46.40 | 1.09 |
| 5 | 2965.11 | 59.88 PK | 80.00 | -20.12 | 1.98 H | 225 | 56.01 | 3.87 |
| 6 | 2965.11 | 40.82 AV | 60.00 | -19.18 | 1.98 H | 225 | 36.95 | 3.87 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




| | | | |
|------------------------|--------------|---|--------------------------------|
| Frequency Range | 1GHz ~ 17GHz | Detector Function & Resolution Bandwidth | Peak (PK) / Average (AV), 1MHz |
| Tested by | Vincent Chen | Environmental Conditions | 23°C, 73%RH |
| Test Mode | Mode 1 | | |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2079.00 | 60.34 PK | 80.00 | -19.66 | 2.50 V | 212 | 59.40 | 0.94 |
| 2 | 2079.00 | 47.58 AV | 60.00 | -12.42 | 2.50 V | 212 | 46.64 | 0.94 |
| 3 | 2227.50 | 61.38 PK | 80.00 | -18.62 | 1.99 V | 147 | 60.29 | 1.09 |
| 4 | 2227.50 | 51.39 AV | 60.00 | -8.61 | 1.99 V | 147 | 50.30 | 1.09 |
| 5 | 2964.98 | 58.69 PK | 80.00 | -21.31 | 2.00 V | 222 | 54.82 | 3.87 |
| 6 | 2964.98 | 39.50 AV | 60.00 | -20.50 | 2.00 V | 222 | 35.63 | 3.87 |


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




8 Pictures of Test Arrangements


8.1 Conducted Emissions at Mains Ports



8.2 Radiated Emissions up to 1 GHz



8.3 Radiated Emissions above 1 GHz



Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---